

Tapbouten DIN 933

RVS A2

Maat	Spoed	Sleutelwijdte	Kophoogte	Kernboor voor tapgat	Doorlaatgat (middel)	Lengtes
M3	0,5	5,5	2	2,5	3,4	6, 8, 10, 12, 16
M4	0,7	7	2,8	3,3	4,5	6, 8, 10, 12, 14, 16, 20, 25, 30, 35, 40, 45, 50, 60
M5	0,8	8	3,5	4,2	5,5	6, 8, 10, 12, 16, 20, 25, 30, 35, 40, 45, 50
M6	1	10	4	5	6,6	8, 10, 12, 14, 16, 18, 20, 22, 25, 30, 35, 40, 45, 50, 55, 60, 65
M8	1,25	13	5,3	6,8	9	10, 12, 14, 16, 18, 20, 22, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 90
M10	1,5	17	6,4	8,5	11	12, 14, 16, 18, 20, 22, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 90, 100
M12	1,75	19	7,5	10,2	13,5	16, 20, 22, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 90, 100
M14	2	22	8,8	12	15,5	40, 45, 50, 55, 60, 65, 70, 75, 80
M16	2	24	10	14	17,5	25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 90, 100
M18	2,5	27	11,5	15,5	20	60, 65, 70, 75, 80, 90, 100
M20	2,5	30	12,5	17,5	22	50, 55, 60, 65, 70, 75, 80, 90, 100
M24	3			21	26	70, 75, 80, 90, 100, 110, 120

Maten in mm. Nominale maten; de toleranties staan in de norm.