

Tapbouten DIN 933

10.9 blank

Maat	Spoed	Sleutelwijdte	Kophoogte	Kernboor voor tapgat	Doorlaatgat (middel)	Lengtes
M6	1	10	4	5	6,6	10, 12, 16, 20, 25, 30, 35, 40, 50, 60
M8	1,25	13	5,3	6,8	9	16, 18, 20, 22, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 80
M10	1,5	17	6,4	8,5	11	16, 20, 22, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 90, 100
M12	1,75	19	7,5	10,2	13,5	16, 20, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 80, 90, 100
M14	2	22	8,8	12	15,5	35, 40
M16	2	24	10	14	17,5	20, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 90, 100
M20	2,5	30	12,5	17,5	22	30, 40, 45, 50, 55, 60, 65, 70, 75, 80, 90, 100
M24	3	36	15	21	26	40, 45, 50, 55, 60, 65, 70, 75, 80, 90, 100

Maten in mm. Nominale maten; de toleranties staan in de norm.