225-3 3-jaw puller with self-centering jaws, up to 70 mm spread, 35 mm reach



DESCRIPTION

The 3-jaw puller with self-centering jaws is used for extracting bearings, gears, and discs. It allows for the removal of any component that is mounted on a shaft and is freely accessible from the outside. The specially shaped jaws are connected to a spring. This ensures self-tensioning of the jaws and prevents possible slipping during the extraction process. Thanks to the quick-release mechanism, the jaws can be attached to the component to be pulled in no time. The 3-jaw design guarantees even load distribution and thus a particularly secure grip on the part being extracted.

APPLICATION AREA

To remove bearings, gears, and discs.

BENEFIT

- The spring ensures self-tensioning of the jaws.
- Steckbolts ensure a quick exchange of the jaws.
- 3-jaw provides an even distribution of force and allows for greater pulling forces.

OPERATION

- Press the quick release to open the jaws
- Place the jaws on the component to be removed
- Release the quick release to enable automatic self-tensioning
- Connect the puller to a sliding hammer or a counter stay to disassemble the component

MASTER DATA

GTIN [GTIN]	4021176123429
Country of origin	DE
Material	Tool steel
Series	225-0
Gross weight [kg]	1,22 kg
Package contents	1 piece
Packaging Act	Rezykkat rHDPE 61
Worldwide sales capability	Yes (REACH, RoHS, POP, PROP65, TSCA)

SPARE PARTS

- 225-3-90-S_3 puller set
- 225-3-A Thread adapter Ag M12 / Ag 15/16 G
- 225-57-S_Set (3 pieces) stud bolts for 225-1/-2/-3 and 225-Sk

DETAIL IMAGE

