129-2 Ball joint press with force-amplifying lever, universal for cars, vans, trucks, with 16 mm jaw opening, 3 t



DESCRIPTION

The Ball joint press with lever transmission of the 129 series is used to press out the ball studs when removing Ball joints as well as tie rod ends on tie rods, universally for car, vans and medium Truck. Thanks to its lever transmission, the Ball joint press can apply a lot of force even where there is hardly any access space available. The 129 series impresses with its versatility of applications. The lever clamping range can be adjusted via the thread of the center spindle.

APPLICATION AREA

For pressing out the ball studs when removing ball joints as well as tie rod ends on tie rods

BENEFIT

- The ball joint puller is universally applicable through three jaw widths.
- The bolt can be adjusted to flexibly adapt the clamping range.

OPERATION

- Attach press between ball joint and component
- Tighten spindle with torque wrench
- Thread pin of the ball joint is pressed out of the component

MASTER DATA

GTIN [GTIN]	4021176024771
Country of origin	DE
Material	Tool steel
Series	129-2
Gross weight [kg]	1,13 kg
Package contents	1 piece
Packaging Act	PAPPE PAP 21
Worldwide sales capability	Yes (REACH, RoHS, POP, PROP65, TSCA)

SPARE PARTS

- 129214_Body
- 129226_Adjusting screw
- 129231_Pull Lever
- 616038_Center spindle