129-6 Truck ball joint press "Universal", with 25 mm jaw opening, 10 t max. tension force



DESCRIPTION

The truck ball joint press "Universal" of series 129 is used for pressing out particularly firmly seated ball pins when removing ball joints on push and steering rods for trucks, buses, and construction vehicles. The series 129 impresses with its versatility.

APPLICATION AREA

To express particularly stubborn ball pins during the removal of ball joints on push and tie rods for trucks, buses, and construction vehicles.

BENEFIT

- Versatile due to the three different separator jaws included in the scope of delivery.
- Especially suitable for solving ball joint connections that are stuck in the cone seat.

OPERATION

- Attach the press between the ball joint and the component
- Tighten the spindle with a torque wrench
- The threaded pin of the ball joint is pushed out of the component

MASTER DATA

GTIN [GTIN]	4021176971662
Country of origin	DE
Material	Tool steel
Series	129-6
Gross weight [kg]	9,24 kg
Package contents	1 piece
Packaging Act	PAPPE PAP 21
Worldwide sales capability	Yes (REACH, RoHS, POP, PROP65, TSCA)

SPARE PARTS

- 1296026_jaw
- 1296126_jaw
- 129614_Body
- 129617_Cap 52X47 for T- 129-6
- 1296226_jaw opening
- 626130_spindle