

HELICOIL® Plus Free Running thread inserts

Stainless steel A2 | coloured green | Metric standard thread

Advantages:

- High thread loading
- Increased quality and value
- Wear-resistant, low and constant thread friction
- Highly resilient
- Corrosion and temperature resistant
- Cost-effective
- Tight fit



Technical information can be found on the last page.

Diameter (d)	Article number	Pitch (P)	D _{HC} min.	D _{1HC} min. max.		Nominal length t ₂ (x d)	Nominal length t ₂	W	t ₃ max.	B	d ₁ min. max.	
M 2	41300020002	0.40	2.52	2.09	2.18	1.00	2.00	2.9	1.8	2.10	2.60	2.80
	41300020003					1.50	3.00	4.9	2.8			
	41300020004					2.00	4.00	6.9	3.8			
	41300020005					2.50	5.00	8.9	4.8			
	41300020006					3.00	6.00	10.9	5.8			
M 2.5	41300250005	0.45	3.08	2.60	2.70	2.00	5.00	8.1	4.8	2.60	3.30	3.50
	41300250025					1.00	2.50	3.5	2.3			
	41300250075					3.00	7.50	12.9	7.3			
	41300250375					1.50	3.75	5.9	3.5			
	41300250625					2.50	6.25	10.5	6.0			
M 3	41300030003	0.50	3.65	3.11	3.22	1.00	3.00	3.9	2.7	3.20	3.80	4.00
	41300030006					2.00	6.00	8.7	5.7			
	41300030009					3.00	9.00	13.5	8.7			
	41300030045					1.50	4.50	6.3	4.2			
	41300030075					2.50	7.50	11.1	7.2			
M 3.5	41300350007	0.60	4.28	3.63	3.76	2.00	7.00	8.7	6.7	3.70	4.42	4.60
	41300350035					1.00	3.50	3.7	3.2			
	41300350053					1.50	5.25	6.3	5.0			
M 4	41300040004	0.70	4.91	4.15	4.29	1.00	4.00	3.7	3.6	4.20	5.05	5.25
	41300040006					1.50	6.00	6.1	5.6			
	41300040008					2.00	8.00	8.4	7.6			
	41300040010					2.50	10.00	10.9	9.6			
	41300040012					3.00	12.00	13.2	11.6			
M 5	41300050005	0.80	6.04	5.17	5.33	1.00	5.00	4.3	4.6	5.20	6.35	6.60
	41300050010					2.00	10.00	9.7	9.6			
	41300050015					3.00	15.00	14.6	14.6			
	41300050075					1.50	7.50	6.9	7.1			
	41300050125					2.50	12.50	12.3	12.1			
M 6	41300060006	1.00	7.30	6.22	6.41	1.00	6.00	4.2	5.5	6.30	7.60	7.85
	41300060009					1.50	9.00	6.9	8.5			
	41300060012					2.00	12.00	9.6	11.5			
	41300060015					2.50	15.00	12.3	14.5			
	41300060018					3.00	18.00	14.6	17.5			

All technical data refer to the measure mm



HELICOIL® Plus Free Running thread inserts

Stainless steel A2 | coloured green | Metric standard thread

Diameter (d)	Article number	Pitch (P)	D _{HC} min.	D _{1HC} min. max.		Nominal length t ₂ (x d)	Nominal length t ₂	W	t ₃ max.	B	d ₁ min. max.	
M 7	41300070007	1.00	8.30	7.22	7.41	1.00	7.00	5.3	6.5	7.30	8.65	8.90
	41300070014					2.00	14.00	11.1	13.5			
	41300070021					3.00	21.00	17.4	20.5			
	41300070105					1.50	10.50	8.2	10.0			
M 8	41300080008	1.25	9.62	8.27	8.48	1.00	8.00	4.7	7.4	8.40	9.85	10.10
	41300080012					1.50	12.00	7.4	11.4			
	41300080016					2.00	16.00	10.6	15.4			
	41300080020					2.50	20.00	13.5	19.4			
M 9	41300080024					3.00	24.00	16.4	23.4			
	41300090009	1.25	10.62	9.27	9.48	1.00	9.00	5.3	8.4	9.40	10.85	11.10
	41300090018					2.00	18.00	11.9	17.4			
	41300090027					3.00	27.00	18.1	26.4			
	41300090135					1.50	13.50	8.6	12.9			
M 10	41300090225					2.50	22.50	15.3	21.9			
	41300100010	1.50	11.95	10.32	10.56	1.00	10.00	5.0	9.2	10.50	12.10	12.50
	41300100015					1.50	15.00	8.1	14.2			
	41300100020					2.00	20.00	11.2	19.2			
	41300100025					2.50	25.00	14.2	24.2			
M 11	41300100030					3.00	30.00	17.2	29.2			
	41300110011	1.50	12.95	11.33	11.56	1.00	11.00	5.6	10.2	11.50	13.10	13.50
	41300110022					2.00	22.00	12.3	21.2			
	41300110033					3.00	33.00	19.1	32.2			
	41300110165					1.50	16.50	9.0	15.7			
M 12	41300110275					2.50	27.50	15.7	26.7			
	41300120012	1.75	14.27	12.38	12.64	1.00	12.00	5.2	11.1	12.50	14.40	14.80
	41300120018					1.50	18.00	8.4	17.1			
	41300120024					2.00	24.00	11.7	23.1			
	41300120030					2.50	30.00	14.7	29.1			
M 14	41300120036					3.00	36.00	18.0	35.1			
	41300140014	2.00	16.60	14.43	14.73	1.00	14.00	5.6	13.0	14.50	16.80	17.20
	41300140021					1.50	21.00	8.8	20.0			
	41300140028					2.00	28.00	12.0	27.0			
	41300140035					2.50	35.00	15.2	34.0			
M 16	41300160016	2.00	18.60	16.43	16.73	1.00	16.00	6.5	15.0	16.50	19.00	19.40
	41300160024					1.50	24.00	10.1	23.0			
	41300160032					2.00	32.00	13.8	31.0			
	41300160040					2.50	40.00	17.5	39.0			
M 18	41300180009	2.50	21.25	18.54	18.90	0.50	9.00	2.3	7.7	18.75	21.50	22.00
	41300180018					1.00	18.00	5.6	16.7			
	41300180027					1.50	27.00	9.0	25.7			
	41300180036					2.00	36.00	12.3	34.7			
M 20	41300200010	2.50	23.25	20.54	20.90	0.50	10.00	2.7	8.7	20.75	23.70	24.20
	41300200015					0.80	15.00	4.5	13.7			
	41300200020					1.00	20.00	6.3	18.7			
	41300200030					1.50	30.00	10.0	28.7			
M 22	41300200040					2.00	40.00	13.7	38.7			
	41300220022	2.50	25.25	22.54	22.90	1.00	22.00	6.9	20.7	22.75	26.30	26.80
	41300220033					1.50	33.00	10.9	31.7			
M 24	41300220044					2.00	44.00	15.0	42.7			
	41300240018	3.00	27.90	24.65	25.05	0.75	18.00	4.5	16.5	24.75	28.60	29.10
	41300240024					1.00	24.00	6.2	22.5			
	41300240036					1.50	36.00	10.0	34.5			
	41300240048					2.00	48.00	14.0	46.5			

All technical data refer to the measure mm



Böllhoff Group · Archimedesstr. 1-4 · 33649 Bielefeld · Phone: +49 521 4482-1387 · fat@boellhoff.com · eshop.boellhoff.de/en/home

This document was generated automatically. Subject to technical changes and errors. Distribution as well as duplication of this document, its utilisation and communication of its content only permitted with express consent.

HELICOIL® Plus Free Running thread inserts


Stainless steel A2 | coloured green | Metric standard thread

Diameter (d)	Article number	Pitch (P)	D _{HC} min.	D _{1HC} min. max.		Nominal length t ₂ (x d)	Nominal length t ₂	W	t ₃ max.	B	d ₁ min. max.	
M 27	41300270027	3.00	30.90	27.65	28.05	1.00	27.00	7.1	25.5	27.75	32.20	32.70
	41300270054					2.00	54.00	15.4	52.5			
	41300270405					1.50	40.50	11.4	39.0			
M 30	41300300030	3.50	34.55	30.76	31.21	1.00	30.00	7.0	27.2	31.00	35.20	35.70
	41300300045					1.50	45.00	11.0	43.2			
	41300300060					2.00	60.00	14.9	58.2			
M 33	41300330033	3.50	37.55	33.76	34.21	1.00	33.00	7.8	31.2	34.00	38.30	38.80
	41300330066					2.00	66.00	16.5	64.2			
	41300330495					1.50	49.50	12.2	47.7			
M 36	41300360036	4.00	41.20	36.87	37.34	1.00	36.00	7.0	34.0	37.00	42.10	42.60
	41300360054					1.50	54.00	11.1	52.0			
	41300360072					2.00	72.00	15.2	70.0			
M 39	41300390078	4.00	44.20	39.87	40.34	2.00	78.00	16.6	72.1	40.00	45.10	45.60
	41300390585					1.50	58.50	12.3	52.6			

All technical data refer to the measure mm




HELICOIL® Plus thread inserts






W and d_1 are the control values for thread inserts (Free Running and Screwlock) before they have been installed. The length can only be measured for installed thread inserts.

Holding thread



Assembly



Prior to tapping, counter-bore 90° and deburr.
Outside diameter of **countersink** = $D_{HC} + 0.1 \text{ mm}$.

- | | |
|---|--|
| d = Nominal thread diameter | t_1 = Minimum depth of tapped hole according to DIN 76 – Part 1 (guide value) |
| P = Thread pitch | t_2 = The nominal length of the thread insert corresponds to the minimum length of the full parent thread for blind holes or the minimum plate thickness for a through hole. |
| d_1 = Outside diameter of thread insert prior to installation | t_3 = Maximum screw-in depth when the tang is not removed |
| W = Number of threads prior to installation | t_5 = Distance of the thread insert from the joint face = 0.25 to 0.5 P, if t_2 corresponds to the above-mentioned minimum value |
| D_{HC} = Outside diameter of the parent thread | |
| D_{1HC} = Crest diameter | |
| B = Suitable twist drill diameter. Please note: D_{1HC} is critical for selecting the correct twist drill diameter. | |

When you use HELICOIL® Plus thread inserts for volume production, we recommend to add at least $1 \times P$ to values t_1 and t_2 .