

Set screws hex socket, flat point ISO 4026

45H bright

Size	Pitch	Hex key	Lengths
M2	0.4	0.9	2, 3, 4
M2.5	0.45	1.3	3, 4, 5, 6, 8
M3	0.5	1.5	3, 4, 5, 6, 8, 10, 12, 14, 16
M4	0.7	2	3, 4, 5, 6, 8, 10, 12, 16, 20
M5	0.8	2.5	4, 5, 6, 8, 10, 12, 16, 20, 25
M6	1	3	5, 6, 8, 10, 12, 14, 16, 20, 25, 30
M8	1.25	4	6, 8, 10, 12, 14, 16, 20, 25, 30, 35, 40, 45, 50, 55
M10	1.5	5	10, 12, 16, 20, 25, 30, 35, 40, 45, 50, 60, 65, 70, 80
M12	1.75	6	10, 12, 16, 20, 25, 30, 35, 40, 45, 50, 55, 60, 70
M16	2		16, 20, 25, 30, 35, 40, 45, 50, 55, 60, 70, 90
M20	2.5		20, 25, 30, 35, 40, 45, 50, 60, 70, 80, 90
M24	3		25, 30, 35, 40, 45, 55, 60, 70, 80, 90, 100

Dimensions in mm. Nominal sizes; tolerances are given in the standard.