

Zylinderstifte gehärtet DIN 6325

Stahl blank

Größe	Längen
1,5	5, 6, 8, 10, 12, 14, 16
2	6, 8, 10, 12, 14, 16, 18, 20
2,5	6, 8, 10, 12, 14, 16, 18, 20
3	6, 8, 10, 12, 14, 16, 18, 20, 22, 24, 26, 28, 30
4	8, 10, 12, 14, 16, 18, 20, 22, 24, 26, 28, 30, 32, 36, 40
5	10, 12, 14, 16, 18, 20, 22, 24, 26, 28, 30, 32, 36, 40, 45, 50
6	12, 14, 16, 18, 20, 22, 24, 26, 28, 30, 32, 36, 40, 45, 50, 55, 60
8	16, 18, 20, 22, 24, 26, 28, 30, 32, 36, 40, 45, 50, 55, 60, 70, 80
10	20, 22, 24, 26, 28, 30, 32, 36, 40, 45, 50, 60, 70, 80, 90
12	24, 26, 28, 30, 32, 36, 40, 45, 50, 55, 60, 70, 80, 90, 100
16	40, 45, 50, 55, 60, 70, 80, 90, 100

Maße in mm. Nennmaße; die Toleranzen stehen in der Norm.