

Maschinenschrauben Zylinderkopf Schlitz

DIN 84

4.8 verzinkt

Größe	Steigung	Kopfhöhe	Kopfdurchmesser	Kernlochbohrer	Durchgangsloch (mittel)	Längen
M2	0,4	1,3	3,8	1,6	2,4	4, 5, 6, 8, 10, 16
M2,5	0,45	1,6	4,5	2,05	2,9	5, 6, 8, 10, 12, 16
M3	0,5			2,5	3,4	4, 5, 6, 8, 10, 12, 14, 16, 18, 20, 25, 30, 35, 40, 45, 50
M3,5	0,6	2,4	6	2,9	3,9	6, 10, 16, 25
M4	0,7			3,3	4,5	5, 6, 8, 10, 12, 14, 16, 18, 20, 22, 25, 30, 35, 40, 45, 50, 55, 60
M5	0,8			4,2	5,5	6, 8, 10, 12, 16, 18, 20, 22, 25, 30, 35, 40, 50
M6	1			5	6,6	8, 10, 12, 16, 18, 20, 25, 30, 35, 40, 45, 50, 60
M8	1,25			6,8	9	16, 20, 25, 30, 40, 50
M10	1,5	6	16	8,5	11	16, 20, 25, 30

Maße in mm. Nennmaße; die Toleranzen stehen in der Norm.