30-10xSP 3-jaw universal puller with narrow, quick-adjustable jaws as a set, up to 130 mm span, 350 mm reach



DESCRIPTION

The 3-jaw universal puller with narrow, quick adjustment jaws is used for the safe extraction of bearings, gears, and discs. Equipped with three pairs of jaws in different lengths, it allows extraction operations with various combinations and depths. This allows any component seated on a shaft and externally accessible to be extracted. The narrow jaws ensure that even tight and hard-to-reach spaces are accessible. The 3-jaw configuration guarantees even load distribution and thus particularly secure grip on the part to be extracted. The Soft-Touch knurls ensure maximum comfort of use even with wet or oily hands.

APPLICATION AREA

To safely remove bearings, gears, and discs.

BENEFIT

- The slender design of the jaws grips optimally on narrow and hard-to-reach areas.
- 3-jaw ensures an even distribution of force and allows for greater pulling forces.
- Application also for eccentric components through freely movable, sliding puller jaws on the crossbar.
- Shear-resistant suspension of the claw in the sliding piece (jaw lock Technology)
- Hexagonal profile on the crossbar for secure counter-holding
- Variable adjustment to any span between 8 mm – 130 mm
- Spindle extension for the protection of the thread
- Safe setup of the spindle through a swivel spindle tip on both smooth surfaces and during centering (Switch Technology)
- Optional convertible from an External Puller to an Internal Extractor by flipping the Jaws.
- Anti-slip safety (spindle neck) at the spindle head for safe work with wrench.
- Jaws, spindle, and crossbar have a spare part number for easy reordering.
- Pullers are labeled with technical attributes and manufacturer information (label)

OPERATION

- Attach the jaws from outside to the part to be pulled off - Slide the claw under the component - Use a wrench to secure the jaws - Manually pull the spindle to apply pressure - Move the hexagon at the spindle head with a ratchet or a wrench until the component is released

MASTER DATA

GTIN [GTIN]	4021176080487
Country of origin	DE
Material	Tool steel
Series	30xSP
Gross weight [kg]	1,54 kg
Package contents	1 piece
Packaging Act	PAPPE PAP 21
Worldwide sales capability	Yes (REACH, RoHS, POP, PROP65, TSCA)

SPARE PARTS

- 1-93-Sx_3 narrow, quick adjustment jaws (set)
- 1-193-Sx_3 narrow, quick-adjustable jaws (set)
- 1-253-Sx_3 narrow, quick adjustable jaws (set)
- 1-V-100-S_3 puller extensions (set)
- 1-V-150-S_3 puller extensions (set)
- 30-10-T_Crossbar
- 612140_Double-sided spindle tip
- 614135_Mechanical Drive Spindle

3-jaw universal puller with narrow, quick-adjustable jaws as a set, up to 130 mm span, 350 mm reach





Abbreviation	Attribut	Wert
X	Total width [mm]	174 mm
Y	Total depth [mm]	174 mm
Z	Total height [mm]	158 mm
A	Clamping depth of external puller [mm]	350 mm
S1	Width across flats [mm]	17 mm
Cmin	Span outside pull-off (min.) [mm]	8 mm
Cmax	Span outside pull-off (max.) [mm]	130 mm
A1	Clamping depth of external pull-off A1 [mm]	200 mm
A2	Clamping depth outside pull-off A2 [mm]	250 mm
A3	Clamping depth external pull-off A3 [mm]	350 mm
K	Hook root thickness at the tip (claw thickness K) [mm]	3 mm
J	Hook base width (claw width J) [mm]	30 mm
O	Hook base depth usable (claw depth usable O) [mm]	9,5 mm
H	Total hook root depth (total claw depth H) [mm]	13 mm
L	Total claw thickness (L+1mm) [mm]: (claw distance to base surface)	2,6 mm
Emin	Span inside pull-out (min.) [mm]	70 mm
Emax	Span inside pull-out (max.) [mm]	180 mm
Tmax	Max. torque [Nm]	40 Nm
Fmax	Max. tractive force [t]	3 t
Fmax	Max. tensile force [kN]	30 kN

Abbreviation	Attribut	Wert
X	Total width [mm]	174 mm
Y	Total depth [mm]	174 mm
Z	Total height [mm]	158 mm
A	Clamping depth of external puller [mm]	350 mm
S1	Width across flats [mm]	17 mm
Cmin	Span outside pull-off (min.) [mm]	8 mm
Cmax	Span outside pull-off (max.) [mm]	130 mm
A1	Clamping depth of external pull-off A1 [mm]	200 mm
A2	Clamping depth outside pull-off A2 [mm]	250 mm
A3	Clamping depth external pull-off A3 [mm]	350 mm
K	Hook root thickness at the tip (claw thickness K) [mm]	3 mm
J	Hook base width (claw width J) [mm]	30 mm
O	Hook base depth usable (claw depth usable O) [mm]	9,5 mm
H	Total hook root depth (total claw depth H) [mm]	13 mm
L	Total claw thickness (L+1mm) [mm]: (claw distance to base surface)	2,6 mm
Emin	Span inside pull-out (min.) [mm]	70 mm
Emax	Span inside pull-out (max.) [mm]	180 mm
Tmax	Max. torque [Nm]	40 Nm
Fmax	Max. tractive force [t]	3 t
Fmax	Max. tensile force [kN]	30 kN



30-SP_Datenzeichnung (Erweiterung)

Abbreviation	Attribut	Wert
X	Total width [mm]	174 mm
Y	Total depth [mm]	174 mm
Z	Total height [mm]	158 mm
A	Clamping depth of external puller [mm]	350 mm
S1	Width across flats [mm]	17 mm
Cmin	Span outside pull-off (min.) [mm]	8 mm
Cmax	Span outside pull-off (max.) [mm]	130 mm
A1	Clamping depth of external pull-off A1 [mm]	200 mm
A2	Clamping depth outside pull-off A2 [mm]	250 mm
A3	Clamping depth external pull-off A3 [mm]	350 mm
K	Hook root thickness at the tip (claw thickness K) [mm]	3 mm
J	Hook base width (claw width J) [mm]	30 mm
O	Hook base depth usable (claw depth usable O) [mm]	9,5 mm
H	Total hook root depth (total claw depth H) [mm]	13 mm
L	Total claw thickness (L+1mm) [mm]: (claw distance to base surface)	2,6 mm
Emin	Span inside pull-out (min.) [mm]	70 mm
Emax	Span inside pull-out (max.) [mm]	180 mm
Tmax	Max. torque [Nm]	40 Nm
Fmax	Max. tractive force [t]	3 t
Fmax	Max. tensile force [kN]	30 kN