

Inbusbouten met cilinderkop DIN 912

10.9 blank

Maat	Spoed	Inbussleutel	Kophoogte	Kopdiameter	Kernboor voor tapgat	Doorlaatgat (middel)	Lengtes
M3	0,5	2,5	3	5,5	2,5	3,4	6, 8, 10, 12, 16, 20, 25
M4	0,7	3	4	7	3,3	4,5	6, 8, 10, 12, 16, 20, 25, 30
M5	0,8	4	5	8,5	4,2	5,5	8, 10, 12, 14, 16, 18, 20, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 80, 85, 90, 100, 150
M6	1	5	6	10	5	6,6	10, 12, 14, 16, 18, 20, 22, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 85, 90, 100, 110, 120
M8	1,25	6	8	13	6,8	9	12, 16, 20, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 85, 90, 95, 100, 110, 120, 130
M10	1,5	8	10	16	8,5	11	16, 20, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 90, 100, 110, 120, 125, 130, 140, 150, 160, 170
M12	1,75	10	12	18	10,2	13,5	20, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 85, 90, 100, 110, 120, 125, 130, 140, 150, 160, 170, 180
M14	2	12	14	21	12	15,5	25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 90, 100, 110, 120, 125, 130, 140, 150
M16	2	14	16	24	14	17,5	25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 90, 100, 110, 120, 130, 140, 150, 160, 170, 180
M18	2,5	14	18	27	15,5	20	50, 55, 60, 70, 75, 80, 90, 100, 110
M20	2,5	17	20	30	17,5	22	35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 85, 90, 100, 110, 120, 130, 140, 150, 160, 170, 180, 190, 200, 210, 220
M24	3	19	24	36	21	26	50, 60, 70, 80, 90, 100, 110, 120, 130, 140, 150, 160, 180, 200, 220

Maten in mm. Nominale maten; de toleranties staan in de norm.