

Hexagon head screws DIN 933

8.8 zinc-plated

Size	Pitch	Spanner size	Head height	Tap drill	Clearance hole (medium)	Lengths
M3	0.5	5.5	2	2.5	3.4	6, 8, 10, 12, 16
M4	0.7	7	2.8	3.3	4.5	8, 10, 12, 16, 20, 25, 30, 35, 40, 50
M5	0.8	8	3.5	4.2	5.5	8, 10, 12, 14, 16, 20, 25, 30, 35, 40, 45, 50
M6	1	10	4	5	6.6	8, 10, 12, 14, 16, 18, 20, 22, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80
M8	1.25	13	5.3	6.8	9	10, 12, 14, 16, 18, 20, 22, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 90, 100
M10	1.5	17	6.4	8.5	11	12, 16, 18, 20, 22, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 90, 100, 110, 120
M12	1.75	19	7.5	10.2	13.5	16, 20, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 85, 90, 100, 110, 120
M14	2	22	8.8	12	15.5	25, 40, 45, 50, 60, 70
M16	2	24	10	14	17.5	20, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 90, 100, 110, 120, 130, 140
M20	2.5	30	12.5	17.5	22	40, 45, 50, 55, 60, 65, 70, 75, 80, 90, 100
M24	3	36	15	21	26	40, 45, 50, 55, 60, 65, 70, 75, 80, 90, 100

Dimensions in mm. Nominal sizes; tolerances are given in the standard.