118-0 Puller for camshaft wheels, up to 115 mm spread, 43 mm reach, with 4 claws



DESCRIPTION

The camshaft puller with sliding, always parallel puller jaws is used for pulling spoke camshaft wheels in the automotive workshop. Equipped with four special puller jaws, the external puller guarantees particularly safe, non-destructive disassembly.

APPLICATION AREA

To remove camshaft gears in the automotive workshop.

BENEFIT

- Special puller jaws for ideal fitting on camshaft gears
- Anti-slip safety (spindle neck) at the spindle head for safe work with wrench.
- Spindle outlet to protect the thread

OPERATION

- Set the puller jaws from the outside on the part to be removed
- Slide the claws under the component
- Manually pull the spindle for fixation
- Move the hexagon at the spindle head with a ratchet or an open-end wrench until the component is loosened

APPLICATION IMAGE



DETAIL IMAGE



MASTER DATA

GTIN [GTIN]	4021176860904
Country of origin	DE
Material	Tool steel
Series	118
Gross weight [kg]	1,26 kg
Package contents	1 piece
Packaging Act	Rezykkat rHDPE 61
Worldwide sales capability	Yes (REACH, RoHS, POP, PROP65, TSCA)

SPARE PARTS

- 118-A-01_Claw, a
- 118-B-01_Claw, b
- 118-C-01_Claw, c
- 614051_spindle