

Hexagon head screws DIN 933

stainless steel A2

Size	Pitch	Spanner size	Head height	Tap drill	Clearance hole (medium)	Lengths
M3	0.5	5.5	2	2.5	3.4	6, 8, 10, 12, 16
M4	0.7	7	2.8	3.3	4.5	6, 8, 10, 12, 14, 16, 20, 25, 30, 35, 40, 45, 50, 60
M5	0.8	8	3.5	4.2	5.5	6, 8, 10, 12, 16, 20, 25, 30, 35, 40, 45, 50
M6	1	10	4	5	6.6	8, 10, 12, 14, 16, 18, 20, 22, 25, 30, 35, 40, 45, 50, 55, 60, 65
M8	1.25	13	5.3	6.8	9	10, 12, 14, 16, 18, 20, 22, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 90
M10	1.5	17	6.4	8.5	11	12, 14, 16, 18, 20, 22, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 90, 100
M12	1.75	19	7.5	10.2	13.5	16, 20, 22, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 90, 100
M14	2	22	8.8	12	15.5	40, 45, 50, 55, 60, 65, 70, 75, 80
M16	2	24	10	14	17.5	25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 90, 100
M18	2.5	27	11.5	15.5	20	60, 65, 70, 75, 80, 90, 100
M20	2.5	30	12.5	17.5	22	50, 55, 60, 65, 70, 75, 80, 90, 100
M24	3			21	26	70, 75, 80, 90, 100, 110, 120

Dimensions in mm. Nominal sizes; tolerances are given in the standard.