

Socket head cap screws ISO 4762

8.8 zinc-plated thick-film passivated

Size	Pitch	Hex key	Head height	Head diameter	Tap drill	Clearance hole (medium)	Lengths
M4	0.7		1.4		3.3	4.5	8, 10, 12, 16, 20, 25, 30, 35
M5	0.8		1.9		4.2	5.5	8, 10, 12, 16, 20, 25, 30, 35, 40, 45
M6	1		2.3		5	6.6	10, 12, 14, 16, 20, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 80
M8	1.25		3.3		6.8	9	12, 16, 20, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 90
M10	1.5		4		8.5	11	20, 25, 30, 35, 40, 45, 50, 55, 60, 70, 80, 90, 100, 110, 120, 130, 140, 160
M12	1.75		4.8		10.2	13.5	20, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 90, 100
M16	2	14	16	24	14	17.5	30, 35, 40, 45, 50, 55, 60, 65, 70, 80, 90, 100, 110, 120, 130, 140

Dimensions in mm. Nominal sizes; tolerances are given in the standard.