

Senkschrauben mit Innensechskant DIN 7991

8.8 verzinkt

Größe	Steigung	Innensechskant	Kopfdurchmesser	Durchgangsloch		Längen
				Kernlochbohrer	(mittel)	
M3	0,5			2,5	3,4	5, 6, 8, 10, 12, 16, 20, 25, 30
M4	0,7			3,3	4,5	6, 8, 10, 12, 16, 20, 25, 30, 35, 40
M5	0,8			4,2	5,5	8, 10, 12, 14, 16, 18, 20, 25, 30, 35, 40, 45, 50
M6	1			5	6,6	8, 10, 12, 14, 16, 18, 20, 25, 30, 35, 40, 45, 50, 55, 60, 70
M8	1,25			6,8	9	10, 12, 16, 18, 20, 22, 25, 30, 35, 40, 45, 50, 55, 60, 70, 80
M10	1,5			8,5	11	16, 20, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70
M12	1,75	8	24	10,2	13,5	20, 25, 30, 35, 40, 45, 50, 55, 60, 70
M16	2	10	30	14	17,5	30, 40, 50, 55, 60, 70

Maße in mm. Nennmaße; die Toleranzen stehen in der Norm.