

Socket head cap screws DIN 912

10.9 bright

Size	Pitch	Hex key	Head height	Head diameter	Tap drill	Clearance hole (medium)	Lengths
M3	0.5	2.5	3	5.5	2.5	3.4	6, 8, 10, 12, 16, 20, 25
M4	0.7	3	4	7	3.3	4.5	6, 8, 10, 12, 16, 20, 25, 30
M5	0.8	4	5	8.5	4.2	5.5	8, 10, 12, 14, 16, 18, 20, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 80, 85, 90, 100, 150
M6	1	5	6	10	5	6.6	10, 12, 14, 16, 18, 20, 22, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 85, 90, 100, 110, 120
M8	1.25	6	8	13	6.8	9	12, 16, 20, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 85, 90, 95, 100, 110, 120, 130
M10	1.5	8	10	16	8.5	11	16, 20, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 90, 100, 110, 120, 125, 130, 140, 150, 160, 170
M12	1.75	10	12	18	10.2	13.5	20, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 85, 90, 100, 110, 120, 125, 130, 140, 150, 160, 170, 180
M14	2	12	14	21	12	15.5	25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 90, 100, 110, 120, 125, 130, 140, 150
M16	2	14	16	24	14	17.5	25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 90, 100, 110, 120, 130, 140, 150, 160, 170, 180
M18	2.5	14	18	27	15.5	20	50, 55, 60, 70, 75, 80, 90, 100, 110
M20	2.5	17	20	30	17.5	22	35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 85, 90, 100, 110, 120, 130, 140, 150, 160, 170, 180, 190, 200, 210, 220
M24	3	19	24	36	21	26	50, 60, 70, 80, 90, 100, 110, 120, 130, 140, 150, 160, 180, 200, 220

Dimensions in mm. Nominal sizes; tolerances are given in the standard.