

Socket head cap screws DIN 912

10.9 zinc-plated

Size	Pitch	Hex key	Head height	Head diameter	Tap drill	Clearance hole (medium)	Lengths
M4	0.7	3	4	7	3.3	4.5	8, 10, 12, 16, 20, 25, 30, 35, 40
M5	0.8	4	5	8.5	4.2	5.5	8, 10, 12, 16, 20, 25, 30, 35, 40, 45, 50
M6	1	5	6	10	5	6.6	8, 10, 12, 16, 20, 25, 30, 35, 40, 45, 50, 60, 70, 80, 90
M8	1.25	6	8	13	6.8	9	16, 20, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 80, 85, 100
M10	1.5	8	10	16	8.5	11	20, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 80, 90, 100, 110
M12	1.75	10	12	18	10.2	13.5	20, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 90, 100, 110, 120
M16	2	14	16	24	14	17.5	30, 35, 40, 45, 50, 55, 60, 65, 70, 80, 90, 100
M20	2.5	17	20	30	17.5	22	40, 50, 60, 70, 80, 90, 100, 110
M24	3	19	24	36	21	26	80, 90, 100, 110

Dimensions in mm. Nominal sizes; tolerances are given in the standard.