

Zeskantbouten ISO 4014

8.8 verzinkt dik gepassiveerd

Maat	Spoed	Sleutelwijdte	Kernboor voor tapgat	Doorlaatgat (middel)	Lengtes
M6	1	10	5	6,6	30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80
M8	1,25	13	6,8	9	35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 90, 100, 110, 120, 130
M10	1,5	16	8,5	11	35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 90, 100, 110, 120, 130, 140, 150, 160, 170
M12	1,75	18	10,2	13,5	40, 45, 50, 55, 60, 65, 70, 75, 80, 85, 90, 100, 110, 120, 130, 140, 150, 160, 170, 180
M16	2	24	14	17,5	55, 60, 65, 70, 75, 80, 90, 110, 120, 130, 140, 150, 160, 170, 180
M20	2,5	30	17,5	22	70, 80, 90, 100, 110, 120, 130, 140, 150, 160, 170, 180
M24	3	36	21	26	80, 100, 110, 120, 130, 140, 150, 160, 170, 180

Maten in mm. Nominale maten; de toleranties staan in de norm.