

Inbusbouten met cilinderkop DIN 912

8.8 blank

Maat	Spood	Inbussleutel	Kophoogte	Kopdiameter	Kernboor voor tapgat	Doorlaatgat (middel)	Lengtes
M3	0,5	2,5	3	5,5	2,5	3,4	5, 6, 8, 10, 12, 16, 20, 25, 30
M4	0,7	3	4	7	3,3	4,5	6, 8, 10, 12, 14, 16, 18, 20, 22, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70
M5	0,8	4	5	8,5	4,2	5,5	8, 10, 12, 14, 16, 18, 20, 22, 25, 30, 35, 40, 45, 50, 55, 60
M6	1	5	6	10	5	6,6	8, 10, 12, 14, 16, 18, 20, 22, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 85, 90, 95, 100
M8	1,25	6	8	13	6,8	9	10, 12, 14, 16, 18, 20, 22, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 85, 90, 100, 105, 110, 120, 130, 140
M10	1,5	8	10	16	8,5	11	12, 16, 20, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 85, 90, 95, 100, 110, 120, 130, 140, 145, 150
M12	1,75	10	12	18	10,2	13,5	16, 20, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 85, 90, 95, 100, 110, 120, 130, 140, 150, 200
M14	2	12	14	21	12	15,5	25, 30, 35, 40, 45, 50, 55, 60, 100, 120
M16	2	14	16	24	14	17,5	20, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 90, 100, 110, 120, 130, 140, 150, 160
M20	2,5	17	20	30	17,5	22	30, 35, 40, 45, 50, 55, 60, 70, 80, 90, 100, 110, 120, 130, 140, 150, 160
M24	3	19	24	36	21	26	50, 55, 60, 70, 80, 85, 90, 100, 110, 120, 130, 140, 150, 160, 180

Maten in mm. Nominale maten; de toleranties staan in de norm.