

# Sechskantschrauben ISO 4017

8.8 verzinkt dickschichtpassiviert

| Größe      | Steigung | Kopfhöhe | Kernlochbohrer | Durchgangsloch (mittel) | Längen                                                             |
|------------|----------|----------|----------------|-------------------------|--------------------------------------------------------------------|
| <b>M4</b>  | 0,7      | 2,8      | 3,3            | 4,5                     | 8, 10, 12, 16, 18, 20, 25, 30, 35, 40                              |
| <b>M5</b>  | 0,8      | 3,5      | 4,2            | 5,5                     | 8, 10, 12, 14, 16, 18, 20, 22, 25, 30, 35, 40, 45, 50              |
| <b>M6</b>  | 1        | 4        | 5              | 6,6                     | 8, 10, 12, 14, 16, 18, 20, 22, 25, 30, 35, 40, 45, 50, 55, 60, 65  |
| <b>M8</b>  | 1,25     | 5,3      | 6,8            | 9                       | 12, 16, 18, 20, 22, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 80     |
| <b>M10</b> | 1,5      | 6,4      | 8,5            | 11                      | 16, 18, 20, 22, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 90 |
| <b>M12</b> | 1,75     | 7,5      | 10,2           | 13,5                    | 20, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 90, 100        |
| <b>M16</b> | 2        | 10       | 14             | 17,5                    | 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 90, 100                |
| <b>M20</b> | 2,5      | 12,5     | 17,5           | 22                      | 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 90, 100, 110, 120      |
| <b>M24</b> | 3        |          | 21             | 26                      | 40, 55, 65, 70, 80, 90                                             |

Maße in mm. Nennmaße; die Toleranzen stehen in der Norm.