

Tapbouten ISO 4017

8.8 verzinkt dik gepassiveerd

Maat	Spood	Kophoogte	Kernboor voor tapgat	Doorlaatgat (middel)	Lengtes
M4	0,7	2,8	3,3	4,5	8, 10, 12, 16, 18, 20, 25, 30, 35, 40
M5	0,8	3,5	4,2	5,5	8, 10, 12, 14, 16, 18, 20, 22, 25, 30, 35, 40, 45, 50
M6	1	4	5	6,6	8, 10, 12, 14, 16, 18, 20, 22, 25, 30, 35, 40, 45, 50, 55, 60, 65
M8	1,25	5,3	6,8	9	12, 16, 18, 20, 22, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 80
M10	1,5	6,4	8,5	11	16, 18, 20, 22, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 90
M12	1,75	7,5	10,2	13,5	20, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 90, 100
M16	2	10	14	17,5	30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 90, 100
M20	2,5	12,5	17,5	22	30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 90, 100, 110, 120
M24	3		21	26	40, 55, 65, 70, 80, 90

Maten in mm. Nominale maten; de toleranties staan in de norm.