

Tapbouten DIN 933

8.8 blank

Maat	Spoed	Sleutelwijdte	Kophoogte	Kernboor voor tapgat	Doorlaatgat (middel)	Lengtes
M3	0,5	5,5	2	2,5	3,4	8
M4	0,7	7	2,8	3,3	4,5	8, 10, 12, 14, 16, 18, 20, 22, 25, 30, 35, 40, 45, 50, 60
M5	0,8	8	3,5	4,2	5,5	6, 8, 10, 12, 14, 16, 18, 20, 22, 25, 30, 35, 40, 45, 50, 55, 60, 70
M6	1	10	4	5	6,6	8, 10, 12, 14, 16, 18, 20, 25, 30, 35, 40, 45, 50, 55, 60
M8	1,25	13	5,3	6,8	9	10, 12, 16, 18, 20, 25, 30, 35, 40, 45, 50, 55, 60, 70, 80
M10	1,5	17	6,4	8,5	11	12, 16, 18, 20, 22, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 90, 100, 120
M12	1,75	19	7,5	10,2	13,5	16, 20, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 90, 100
M14	2	22	8,8	12	15,5	30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 100
M16	2	24	10	14	17,5	20, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 90, 100, 120
M18	2,5	27	11,5	15,5	20	40, 45, 50, 55, 60, 65, 70, 75, 80, 90, 100
M20	2,5	30	12,5	17,5	22	30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 90, 100, 110, 120
M22	2,5	32	14	19,5	24	40, 45, 50, 55, 60, 65, 70, 75, 80, 90, 100, 110, 120
M24	3	36	15	21	26	40, 45, 50, 55, 60, 65, 70, 75, 80, 90, 100, 110, 120

Maten in mm. Nominale maten; de toleranties staan in de norm.