

Inbusbouten met cilinderkop DIN 912

10.9 verzinkt

Maat	Spoed	Inbussleutel	Kophoogte	Kopdiameter	Kernboor voor tapgat	Doorlaatgat (middel)	Lengtes
M4	0,7	3	4	7	3,3	4,5	8, 10, 12, 16, 20, 25, 30, 35, 40
M5	0,8	4	5	8,5	4,2	5,5	8, 10, 12, 16, 20, 25, 30, 35, 40, 45, 50
M6	1	5	6	10	5	6,6	8, 10, 12, 16, 20, 25, 30, 35, 40, 45, 50, 60, 70, 80, 90
M8	1,25	6	8	13	6,8	9	16, 20, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 80, 85, 100
M10	1,5	8	10	16	8,5	11	20, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 80, 90, 100, 110
M12	1,75	10	12	18	10,2	13,5	20, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 90, 100, 110, 120
M16	2	14	16	24	14	17,5	30, 35, 40, 45, 50, 55, 60, 65, 70, 80, 90, 100
M20	2,5	17	20	30	17,5	22	40, 50, 60, 70, 80, 90, 100, 110
M24	3	19	24	36	21	26	80, 90, 100, 110

Maten in mm. Nominale maten; de toleranties staan in de norm.