

Sechskantschrauben DIN 933

Edelstahl A4

Größe	Steigung	Schlüsselweite	Kopfhöhe	Kernlochbohrer	Durchgangsloch (mittel)	Längen
M5	0,8	8	3,5	4,2	5,5	12, 16, 20, 25, 30
M6	1	10	4	5	6,6	8, 10, 12, 14, 16, 18, 20, 22, 25, 30, 35, 40, 45, 50, 55, 60, 65
M8	1,25	13	5,3	6,8	9	12, 14, 16, 18, 20, 22, 25, 30, 35, 40, 45, 50, 55, 60, 70, 80
M10	1,5	17	6,4	8,5	11	16, 18, 20, 22, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80
M12	1,75	19	7,5	10,2	13,5	25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 90
M14	2	22	8,8	12	15,5	40, 45, 50, 55, 60, 65, 70, 75, 80
M16	2	24	10	14	17,5	25, 30, 40, 45, 50, 55, 60, 65, 70, 75, 80, 90, 100, 120
M18	2,5	27	11,5	15,5	20	70, 75, 80, 90, 100
M20	2,5	30	12,5	17,5	22	40, 50, 60, 80, 90, 100

Maße in mm. Nennmaße; die Toleranzen stehen in der Norm.