

Zylinderschrauben mit Innensechskant DIN 912

8.8 blank

Größe	Steigung	Innensechskant	Kopfhöhe	Kopfdurchmesser	Kernlochbohrer	Durchgangsloch	Längen
						(mittel)	
M3	0,5	2,5	3	5,5	2,5	3,4	5, 6, 8, 10, 12, 16, 20, 25, 30
M4	0,7	3	4	7	3,3	4,5	6, 8, 10, 12, 14, 16, 18, 20, 22, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70
M5	0,8	4	5	8,5	4,2	5,5	8, 10, 12, 14, 16, 18, 20, 22, 25, 30, 35, 40, 45, 50, 55, 60
M6	1	5	6	10	5	6,6	8, 10, 12, 14, 16, 18, 20, 22, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 85, 90, 95, 100
M8	1,25	6	8	13	6,8	9	10, 12, 14, 16, 18, 20, 22, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 85, 90, 100, 105, 110, 120, 130, 140
M10	1,5	8	10	16	8,5	11	12, 16, 20, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 85, 90, 95, 100, 110, 120, 130, 140, 145, 150
M12	1,75	10	12	18	10,2	13,5	16, 20, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 85, 90, 95, 100, 110, 120, 130, 140, 150, 200
M14	2	12	14	21	12	15,5	25, 30, 35, 40, 45, 50, 55, 60, 100, 120
M16	2	14	16	24	14	17,5	20, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 90, 100, 110, 120, 130, 140, 150, 160
M20	2,5	17	20	30	17,5	22	30, 35, 40, 45, 50, 55, 60, 70, 80, 90, 100, 110, 120, 130, 140, 150, 160

Größe	Steigung	Innensechskant	Kopfhöhe	Kopfdurchmesser	Kernlochbohrer	Durchgangsloch	Längen
						(mittel)	
M24	3	19	24	36	21	26	50, 55, 60, 70, 80, 85, 90, 100, 110, 120, 130, 140, 150, 160, 180

Maße in mm. Nennmaße; die Toleranzen stehen in der Norm.