E 1411


EJOT®-PT screws

Raised countersunk head with pressed-on washer | Cruciform drive H (Phillips)



Steel 10 | zinc-plated | Cr(VI)-free | Self-tapping thread

Note: Further information and CAD files can be obtained directly from EJOT: http://www.ejot.com/industry



Diameter (d)	Tool size	d_1 nominal size	d_2 nominal size	k nominal size	s min.	s max.	Pitch (P)	t max.	t min.
2.2	H1	4.4	1.25	1.6	0.5	0.7	0.98	1.14	0.68
2.5	H1	5	1.4	1.8	0.6	0.8	1.12	1.28	0.82
3	H1	6	1.66	2.1	0.7	0.9	1.34	1.61	1.15
3.5	H2	7	1.91	2.4	0.8	1.0	1.57	1.70	1.07
4	H2	8	2.17	2.5	0.9	1.1	1.79	1.96	1.33
5	H2	10	2.68	3.2	1.1	1.3	2.24	2.61	1.98
6	H3	12	3.19	4.0	1.3	1.5	2.69	2.90	2.24

Length (l)		
nominal size	min.	max.
5	4.62	5.38
6	5.62	6.38
8	7.55	8.45
10	9.55	10.45
12	11.45	12.55
14	13.45	14.55

Length (l)		
nominal size	min.	max.
16	15.45	16.55
18	17.45	18.55
20	19.35	20.65
25	24.35	25.65
30	29.35	30.65
35	34.20	35.80

All technical data refer to the measure mm

All technical data without obligation. Subject to technical changes and errors.

E 1411

EJOT®-PT screws

Raised countersunk head with pressed-on washer | Cruciform drive H (Phillips)

Steel 10 | zinc-plated | Cr(VI)-free | Self-tapping thread

Diameter	Length (l)											
(d)	5	6	8	10	12	14	16	18	20	25	30	35
2.2	●											
2.5		●	●	●	●	●						
3		●	●	●	●	●	●	●	●			
3.5			●	●	●	●	●	●	●	●		
4			●	●	●	●	●	●	●	●	●	●
5				●			●	●		●		
6							●					

All technical data refer to the measure mm

All technical data without obligation. Subject to technical changes and errors.