

Inbusbouten met cilinderkop DIN 912

8.8 verzinkt

Maat	Spoed	Inbussleutel	Kophoogte	Kopdiameter	Kernboor voor tapgat	Doorlaatgat (middel)	Lengtes
M2	0,4				1,6	2,4	6, 8, 12
M2,5	0,45	2	2,5	4,5	2,05	2,9	6, 8, 12
M3	0,5	2,5	3	5,5	2,5	3,4	6, 8, 10, 12, 14, 16, 18, 20, 22, 25, 30, 35, 40, 45, 46, 50
M4	0,7	3	4	7	3,3	4,5	5, 6, 8, 10, 12, 14, 16, 18, 20, 22, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 100
M5	0,8	4	5	8,5	4,2	5,5	6, 8, 10, 12, 14, 16, 18, 20, 22, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 85, 90, 100, 110, 120, 140, 160
M6	1	5	6	10	5	6,6	6, 8, 10, 12, 14, 16, 18, 20, 22, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 85, 90, 95, 100, 110, 120, 130, 140, 150, 160, 180, 190, 200
M8	1,25	6	8	13	6,8	9	10, 12, 14, 16, 18, 20, 22, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 85, 90, 95, 100, 105, 110, 115, 120, 130, 140, 150, 160
M10	1,5	8	10	16	8,5	11	12, 14, 16, 18, 20, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 85, 90, 100, 110, 120, 130, 140, 150, 160, 170
M12	1,75	10	12	18	10,2	13,5	20, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 90, 100, 110, 120, 130, 140, 150, 160
M14	2	12	14	21	12	15,5	25, 30, 35, 40, 45, 50, 55, 60, 65, 70
M16	2	14	16	24	14	17,5	25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 90, 100, 110, 120, 130, 140, 150, 160
M20	2,5	17	20	30	17,5	22	30, 35, 40, 45, 50, 55, 60, 65, 70, 80, 90
M24	3	19	24	36	21	26	50, 55, 60, 70, 80, 90, 100

Maten in mm. Nominale maten; de toleranties staan in de norm.