

# Metaalschroeven verzonken kop kruiskop

## PH DIN 965

4.8 verzinkt

| Maat        | Spoed | Bit | Kophoogte | Kernboor voor tapgat | Doorlaatgat (middel) | Lengtes                                |
|-------------|-------|-----|-----------|----------------------|----------------------|----------------------------------------|
| <b>M2</b>   | 0,4   | PH1 | 1,2       | 1,6                  | 2,4                  | 4, 6, 8                                |
| <b>M2,5</b> | 0,45  | PH1 | 1,5       | 2,05                 | 2,9                  | 5, 6, 8, 10, 16, 20                    |
| <b>M3</b>   | 0,5   |     |           | 2,5                  | 3,4                  | 4, 6, 8, 10, 12, 16, 20, 25, 30        |
| <b>M4</b>   | 0,7   |     |           | 3,3                  | 4,5                  | 5, 6, 8, 10, 12, 16, 20, 25, 30, 40    |
| <b>M5</b>   | 0,8   |     |           | 4,2                  | 5,5                  | 8, 10, 12, 16, 20, 25, 30, 35, 40      |
| <b>M6</b>   | 1     |     |           | 5                    | 6,6                  | 10, 12, 16, 20, 25, 30, 35, 40, 45, 50 |
| <b>M8</b>   | 1,25  |     |           | 6,8                  | 9                    | 10, 12, 16, 20, 25, 30                 |

Maten in mm. Nominale maten; de toleranties staan in de norm.