

## Spring washers wave DIN 137 B

spring steel bright

| Size       | Pitch | Inner diameter | Outer diameter | Thickness |
|------------|-------|----------------|----------------|-----------|
| <b>M3</b>  | 0.5   | 3.2            | 8              | 1.6       |
| <b>M4</b>  | 0.7   | 4.3            | 9              | 2         |
| <b>M5</b>  | 0.8   | 5.3            | 11             | 2.2       |
| <b>M6</b>  | 1     | 6.4            | 12             | 2.6       |
| <b>M7</b>  | 1     | 7.4            | 14             | 3         |
| <b>M8</b>  | 1.25  | 8.4            | 15             | 3         |
| <b>M10</b> | 1.5   | 10.5           | 21             | 4.2       |
| <b>M12</b> | 1.75  | 13             | 24             | 5         |
| <b>M14</b> | 2     | 15             | 28             | 6         |
| <b>M16</b> | 2     | 17             | 30             | 6.4       |
| <b>M18</b> | 2.5   | 19             | 34             | 6.6       |
| <b>M20</b> | 2.5   | 21             | 36             | 7.4       |
| <b>M22</b> | 2.5   | 23             | 40             | 7.8       |
| <b>M24</b> | 3     | 25             | 44             | 8.2       |

Dimensions in mm. Nominal sizes; tolerances are given in the standard.