

Inbusbouten met cilinderkop DIN 912

RVS A4

Maat	Spoed	Inbussleutel	Kophoogte	Kopdiameter	Kernboor voor tapgat	Doorlaatgat (middel)	Lengtes
M1,4							4
M2	0,4	1,5	2	3,8	1,6	2,4	4, 5, 6
M2,5	0,45	2	2,5	4,5	2,05	2,9	5, 6, 8
M3	0,5	2,5	3	5,5	2,5	3,4	5, 6, 8, 10, 12, 14, 16
M4	0,7	3	4	7	3,3	4,5	6, 8, 10, 12, 14, 16, 20, 25, 30, 35, 40, 45
M5	0,8	4	5	8,5	4,2	5,5	6, 8, 10, 12, 14, 16, 20, 22, 25, 30, 35, 40, 45, 50
M6	1	5	6	10	5	6,6	10, 12, 14, 16, 20, 25, 30, 35, 40, 45, 50, 55
M8	1,25	6	8	13	6,8	9	12, 14, 16, 20, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80
M10	1,5	8	10	16	8,5	11	16, 20, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 80, 90
M12	1,75	10	12	18	10,2	13,5	20, 25, 30, 35, 40, 45, 50, 60, 70, 80, 100
M16	2	14	16	24	14	17,5	30, 35, 40, 45, 50, 55, 60, 70, 80, 90, 100

Maten in mm. Nominale maten; de toleranties staan in de norm.