129-25 Universal ball joint press, with 19 mm jaw opening, 17 t max. tension force



DESCRIPTION

The universal ball joint puller of the series 129 is used for pressing out the ball pins when removing ball joints on tie rods and track rods in passenger cars. Thanks to its leverage, the ball joint puller can also apply a lot of force where there is hardly any access space. The series 129 impresses with its wide range of applications. The lever clamping range can be adjusted via the thread of the center spindle.

APPLICATION AREA

To express the ball joints during the removal of ball joints on thrust and tie rods in passenger cars.

BENEFIT

- With the center spindle, the press can be adjusted and pre-tensioned.
- The bolt can be adjusted to flexibly adapt the clamping range.
- The spread can be adjusted threefold by a simple modification.

OPERATION

- Attach press between ball joint and component
- Tighten spindle with torque wrench
- Thread pin of the ball joint is pressed out of the component

MASTER DATA

GTIN [GTIN]	4021176967924
Country of origin	DE
Material	Tool steel
Series	129-25
Gross weight [kg]	1,62 kg
Package contents	1 piece
Packaging Act	PAPPE PAP 21
Worldwide sales capability	Yes (REACH, RoHS, POP, PROP65, TSCA)

SPARE PARTS

- 1292514_Körper
- 1292526_adjusting screw
- 1292531_lever
- 1292557_dowel pin