225-SK-G 3-jaw puller with self-centering jaws, sliding hammer, up to 65 mm spread, 24 mm reach



DESCRIPTION

The 3-jaw puller with self-centering jaws and sliding hammer is used for the safe and damage-free removal of pressed-on hub caps, wheel covers, and dust and grease caps. The sliding hammer ensures a space-saving and material-saving extraction. The specially shaped jaws are connected with a spring. This provides self-tensioning of the jaws and prevents possible slippage during the pulling process. Thanks to the quick-release mechanism, the jaws can be easily applied to the component to be pulled. The narrow jaws ensure that even tight and hard-to-reach spaces can be accessed. The 3-jaw design guarantees even load distribution and thus a particularly secure grip on the part to be pulled.

APPLICATION AREA

To safely and without damage remove pushed-on hub caps, wheel covers, as well as dust and grease caps.

BENEFIT

- The spring ensures self-tensioning of the jaws.
- Steckbolts ensure a quick exchange of the jaws.
- 3-jaw provides an even distribution of force and allows for greater pulling forces.
- Narrow puller jaws grip optimally in tight and hard-to-reach places.
- Sliding hammer requires no support surface and guarantees a gentle extraction.
- The shape of the sliding piece allows for a high impact weight of the sliding hammer with simple handling.
- The internal stop point prevents crushing and ensures a safe working process.

OPERATION

- Press the quick release to open the jaws
- Place the jaws on the component to be pulled off
- Release the quick release to enable automatic self-tensioning
- Use the sliding hammer with a striking motion to pull the bearing out

MASTER DATA

GTIN [GTIN]	4021176080074
Country of origin	DE
Material	Tool steel
Series	225-SK-G
Gross weight [kg]	1,9 kg
Package contents	1 piece
Packaging Act	PAPPE PAP 21
Worldwide sales capability	Yes (REACH, RoHS, POP, PROP65, TSCA)

DETAIL IMAGE

