

Machine screws countersunk slotted DIN 963

4.8 zinc-plated

Size	Pitch	Head height	Head diameter	Tap drill	Clearance hole (medium)	Lengths
M2	0.4	1.2	3.8	1.6	2.4	4, 5, 6, 8, 10, 12, 16
M2.5	0.45	1.5	4.7	2.05	2.9	5, 6, 8, 10, 12, 16
M3	0.5	1.65	5.6	2.5	3.4	5, 6, 8, 10, 12, 16, 20, 25, 30
M4	0.7			3.3	4.5	5, 6, 8, 10, 12, 16, 20, 25, 30, 35, 40
M5	0.8			4.2	5.5	8, 10, 12, 16, 20, 25, 30, 35, 40, 50
M6	1			5	6.6	8, 10, 12, 16, 20, 25, 30, 35, 40, 50
M8	1.25			6.8	9	10, 12, 16, 20, 25, 30, 35, 40, 50
M10	1.5	5	18	8.5	11	16, 18, 20, 22, 25, 30, 35, 40, 45, 50, 60
M12	1.75	6	22	10.2	13.5	20, 25, 30, 35, 40, 45, 50, 60
M16	2	8	29	14	17.5	30, 35, 40, 45, 50, 60

Dimensions in mm. Nominal sizes; tolerances are given in the standard.