

Zeskantbouten DIN 931

10.9 blank

Maat	Spoed	Sleutelwijdte	Kernboor voor tapgat	Doorlaatgat (middel)	Lengtes
M6	1	10	5	6,6	35, 40, 45, 50, 55, 60, 65, 70, 80, 90
M8	1,25	13	6,8	9	35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 90, 100, 110, 120, 130, 140
M10	1,5	17	8,5	11	40, 45, 50, 55, 60, 65, 70, 75, 80, 90, 100, 110, 120, 130, 140, 150, 160, 170, 180
M12	1,75	19	10,2	13,5	45, 50, 55, 60, 65, 70, 75, 80, 85, 90, 100, 110, 120, 130, 140, 150, 160, 170, 180
M16	2	24	14	17,5	50, 55, 60, 65, 70, 75, 80, 90, 100, 110, 120, 130, 140, 150, 160, 170, 180
M20	2,5	30	17,5	22	65, 70, 75, 80, 90, 100, 110, 120, 130, 140, 150, 160, 170, 180
M24	3	36	21	26	75, 80, 90, 100, 110, 120, 130, 140, 150, 160, 170, 180

Maten in mm. Nominale maten; de toleranties staan in de norm.