

Metaalschroeven bolcilinderkop kruiskop PH

DIN 7985

4.8 verzinkt

Maat	Spoed	Bit	Kophoogte	Kopdiameter	Kernboor voor tapgat	Doorlaatgat (middel)	Lengtes
M2	0,4				1,6	2,4	4, 5, 6, 8, 10, 12, 16
M2,5	0,45				2,05	2,9	5, 6, 8, 10, 12, 14, 16, 20, 25
M3	0,5				2,5	3,4	4, 8, 10, 12, 14, 16, 18, 20, 22, 25, 28, 30
M3,5	0,6	PH2	2,7	7	2,9	3,9	6, 8, 25
M4	0,7				3,3	4,5	4, 5, 6, 8, 10, 12, 14, 16, 18, 20, 22, 25, 28, 30, 35, 40, 45, 50, 55, 60
M5	0,8				4,2	5,5	6, 8, 10, 12, 14, 16, 18, 20, 22, 25, 30, 35, 40, 45, 50, 55, 60, 70
M6	1				5	6,6	8, 10, 12, 14, 16, 18, 20, 25, 30, 35, 40, 45, 50, 55, 60, 70
M8	1,25				6,8	9	10, 12, 16, 18, 20, 25, 30, 35, 40, 45, 50, 60, 70

Maten in mm. Nominale maten; de toleranties staan in de norm.