

Inbusbouten met cilinderkop ISO 4762

8.8 verzinkt dik gepassiveerd

Maat	Spoed	Inbussleutel	Kophoogte	Kopdiameter	Kernboor voor tapgat	Doorlaatgat (middel)	Lengtes
M4	0,7		1,4		3,3	4,5	8, 10, 12, 16, 20, 25, 30, 35
M5	0,8		1,9		4,2	5,5	8, 10, 12, 16, 20, 25, 30, 35, 40, 45
M6	1		2,3		5	6,6	10, 12, 14, 16, 20, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 80
M8	1,25		3,3		6,8	9	12, 16, 20, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 90
M10	1,5		4		8,5	11	20, 25, 30, 35, 40, 45, 50, 55, 60, 70, 80, 90, 100, 110, 120, 130, 140, 160
M12	1,75		4,8		10,2	13,5	20, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 90, 100
M16	2	14	16	24	14	17,5	30, 35, 40, 45, 50, 55, 60, 65, 70, 80, 90, 100, 110, 120, 130, 140

Maten in mm. Nominale maten; de toleranties staan in de norm.