

Sechskantschrauben DIN 933

8.8 verzinkt

Größe	Steigung	Schlüsselweite	Kopfhöhe	Kernlochbohrer	Durchgangsloch (mittel)	Längen
M3	0,5	5,5	2	2,5	3,4	6, 8, 10, 12, 16
M4	0,7	7	2,8	3,3	4,5	8, 10, 12, 16, 20, 25, 30, 35, 40, 50
M5	0,8	8	3,5	4,2	5,5	8, 10, 12, 14, 16, 20, 25, 30, 35, 40, 45, 50
M6	1	10	4	5	6,6	8, 10, 12, 14, 16, 18, 20, 22, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80
M8	1,25	13	5,3	6,8	9	10, 12, 14, 16, 18, 20, 22, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 90, 100
M10	1,5	17	6,4	8,5	11	12, 16, 18, 20, 22, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 90, 100, 110, 120
M12	1,75	19	7,5	10,2	13,5	16, 20, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 85, 90, 100, 110, 120
M14	2	22	8,8	12	15,5	25, 40, 45, 50, 60, 70
M16	2	24	10	14	17,5	20, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 90, 100, 110, 120, 130, 140
M20	2,5	30	12,5	17,5	22	40, 45, 50, 55, 60, 65, 70, 75, 80, 90, 100
M24	3	36	15	21	26	40, 45, 50, 55, 60, 65, 70, 75, 80, 90, 100

Maße in mm. Nennmaße; die Toleranzen stehen in der Norm.