128-50 Bell-shaped ball joint puller, with Ø 46 mm jaw opening, 85 mm insertion depth



DESCRIPTION

The bell-shaped ball joint puller of series 128 is used to press out the ball studs when removing ball joints and tie rod ends on tie rods in automotive and industry applications. The puller allows for damage-free working and is optimal when there is plenty of space available. The series 128 impresses with its quick and easy operation and is available in various sizes.

APPLICATION AREA

To express the ball pins when disassembling ball joints and tie rod ends on tie rods in automotive and industry.

BENEFIT

- Due to its simple yet effective design, the direct print ball joint puller is particularly suitable for quick and uncomplicated application.
- The ball joint pullers can be used hydraulically together with the YSM series lift cylinder.

OPERATION

- Attach puller between ball joint and component
- Torque the spindle with torque wrench
- Threaded pin of the ball joint is pushed out of the component

MASTER DATA

GTIN [GTIN]	4021176006982
Country of origin	DE
Material	Tool steel
Series	128-0
Gross weight [kg]	1,9 kg
Package contents	1 piece
Packaging Act	PAPPE PAP 21
Worldwide sales capability	Yes (REACH, RoHS, POP, PROP65, TSCA)

SPARE PARTS

- 128-EP-50_Adapter Plate

APPLICATION IMAGE

