223-3 Dowel pin puller with sliding hammer (5 mm - 20 mm), with 250 mm impact stroke, 1.7 kg impact weight



DESCRIPTION

The Dowel pin puller 223-3 is used for Removing tension and serrated pins in craftsmanship, industry and workshops, as well as in mold making. The three gripping edges can be adjusted to the relevant application in the range of 5–20 mm. The micro serration in the socket enables the holding force to be increased even further to ensure a secure fit. The ergonomically shaped, solid sliding piece allows the applied force to be transferred optimally and a strong shock effect to be achieved. A key is included for effortless clamping and opening. In addition, the key ensures a higher clamping force, which means that even smooth dowel pins can be pulled out.

APPLICATION AREA

To remove dowel pins in craft, industry, and workshop.

BENEFIT

- Universally adjustable spread up to 20 mm
- Increased power development through fine notching of the jaws
- The shape of the sliding piece allows for a high impact weight of the sliding hammer with simple application.
- The internal stop point prevents pinching and ensures a safe working process.
- If there is not enough space available, the impact weight can be reversed.

MASTER DATA

GTIN [GTIN]	4021176024047
Country of origin	DE
Material	Tool steel
Series	223-0
Gross weight [kg]	4,02 kg
Package contents	1 piece
Packaging Act	Rezykkat rHDPE 61
Worldwide sales capability	Yes (REACH, RoHS, POP, PROP65, TSCA)

APPLICATION IMAGE



DETAIL IMAGE

