

Hexagon head screws DIN 933

stainless steel A4

Size	Pitch	Spanner size	Head height	Tap drill	Clearance hole (medium)	Lengths
M5	0.8	8	3.5	4.2	5.5	12, 16, 20, 25, 30
M6	1	10	4	5	6.6	8, 10, 12, 14, 16, 18, 20, 22, 25, 30, 35, 40, 45, 50, 55, 60, 65
M8	1.25	13	5.3	6.8	9	12, 14, 16, 18, 20, 22, 25, 30, 35, 40, 45, 50, 55, 60, 70, 80
M10	1.5	17	6.4	8.5	11	16, 18, 20, 22, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80
M12	1.75	19	7.5	10.2	13.5	25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 90
M14	2	22	8.8	12	15.5	40, 45, 50, 55, 60, 65, 70, 75, 80
M16	2	24	10	14	17.5	25, 30, 40, 45, 50, 55, 60, 65, 70, 75, 80, 90, 100, 120
M18	2.5	27	11.5	15.5	20	70, 75, 80, 90, 100
M20	2.5	30	12.5	17.5	22	40, 50, 60, 80, 90, 100

Dimensions in mm. Nominal sizes; tolerances are given in the standard.