16-21 Internal extractor with spread 60 mm - 155 mm, 190 mm insertion depth



DESCRIPTION

The internal extractor of the series 16 is used in combination with the counter stays 16-22 or 16-23 for pulling bearings and bushings in crafts, industry, and workshops. The multi-shell design of the internal extractor with its extra large gripping edges allows for the safe extraction of internal components. Three spreader bodies guarantee an optimal adaptation of the internal extractor to the respective application.

APPLICATION AREA

To extract cylinder liners and similar parts in trucks, cars, and stationary engines.

BENEFIT

- The robust construction and built-in spindle stop not only ensure strong but also safe work.
- Due to the extraordinary clamping force and the mechanical spindle, even bearings that are closely seated on the back wall are securely and quickly removed.
- The Power Nut minimizes friction resistance while simultaneously allowing forces that can otherwise only be achieved with hydraulic spindles.
- The mechanical spindle allows bearings that are tightly seated on the rear wall to be safely and quickly extracted.

OPERATION

- Screw the spindle of the counter stay into the tension nut of the puller
- Support the counter stay on the engine block and introduce the puller into the cylinder socket
- tighten the tension nut of the puller
- Extract the cylinder socket by tightening the spindle nut of the counter stay

APPLICATION IMAGE



DETAIL IMAGE



MASTER DATA

GTIN [GTIN]	4021176251559
Country of origin	DE
Material	Tool steel
Series	16
Gross weight [kg]	3,47 kg
Package contents	1 piece
Packaging Act	Rezykkat rHDPE 61
Worldwide sales capability	Yes (REACH, RoHS, POP, PROP65, TSCA)

SUITABLE FOR

- 16-22_Counter Stay
- 16-23_Counter Stay

SPARE PARTS

- 16-21-33_3 spreader (set)
- 16-21-6_spindle