

Sechskantschrauben DIN 933

Edelstahl A2

Größe	Steigung	Schlüsselweite	Kopfhöhe	Kernlochbohrer	Durchgangsloch (mittel)	Längen
M3	0,5	5,5	2	2,5	3,4	6, 8, 10, 12, 16
M4	0,7	7	2,8	3,3	4,5	6, 8, 10, 12, 14, 16, 20, 25, 30, 35, 40, 45, 50, 60
M5	0,8	8	3,5	4,2	5,5	6, 8, 10, 12, 16, 20, 25, 30, 35, 40, 45, 50
M6	1	10	4	5	6,6	8, 10, 12, 14, 16, 18, 20, 22, 25, 30, 35, 40, 45, 50, 55, 60, 65
M8	1,25	13	5,3	6,8	9	10, 12, 14, 16, 18, 20, 22, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 90
M10	1,5	17	6,4	8,5	11	12, 14, 16, 18, 20, 22, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 90, 100
M12	1,75	19	7,5	10,2	13,5	16, 20, 22, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 90, 100
M14	2	22	8,8	12	15,5	40, 45, 50, 55, 60, 65, 70, 75, 80
M16	2	24	10	14	17,5	25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 90, 100
M18	2,5	27	11,5	15,5	20	60, 65, 70, 75, 80, 90, 100
M20	2,5	30	12,5	17,5	22	50, 55, 60, 65, 70, 75, 80, 90, 100
M24	3			21	26	70, 75, 80, 90, 100, 110, 120

Maße in mm. Nennmaße; die Toleranzen stehen in der Norm.