

Metaalschroeven cilinderkop zaaggleuf DIN

84

4.8 verzinkt

Maat	Spoed	Kophoogte	Kopdiameter	Kernboor voor tapgat	Doorlaatgat (middel)	Lengtes
M2	0,4	1,3	3,8	1,6	2,4	4, 5, 6, 8, 10, 16
M2,5	0,45	1,6	4,5	2,05	2,9	5, 6, 8, 10, 12, 16
M3	0,5			2,5	3,4	4, 5, 6, 8, 10, 12, 14, 16, 18, 20, 25, 30, 35, 40, 45, 50
M3,5	0,6	2,4	6	2,9	3,9	6, 10, 16, 25
M4	0,7			3,3	4,5	5, 6, 8, 10, 12, 14, 16, 18, 20, 22, 25, 30, 35, 40, 45, 50, 55, 60
M5	0,8			4,2	5,5	6, 8, 10, 12, 16, 18, 20, 22, 25, 30, 35, 40, 50
M6	1			5	6,6	8, 10, 12, 16, 18, 20, 25, 30, 35, 40, 45, 50, 60
M8	1,25			6,8	9	16, 20, 25, 30, 40, 50
M10	1,5	6	16	8,5	11	16, 20, 25, 30

Maten in mm. Nominale maten; de toleranties staan in de norm.