33 Steering wheel puller for steering wheels with narrow pull slots, up to 83 mm spread



DESCRIPTION

The 2-jaw puller is used for removing steering wheels with narrow pull slots. The two short jaws are ideally suited for sports steering wheels. The long jaws are used for standard steering wheels. Due to their construction, the jaws are adjustable in any direction. Thanks to the slim design of the puller, it can reach into narrow pull slots to disassemble the steering wheel or other hard-to-reach components.

APPLICATION AREA

For removing steering wheels with narrow puller slots.

BENEFIT

- Anti-slip safety (spindle neck) at the spindle head for safe working with wrench.
- Spindle outlet to protect the thread
- Universally applicable for a variety of steering wheel types thanks to different lengths of jaws.
- A separate protective cap for the steering column thread is included.

OPERATION

- Remove airbag to be able to remove the steering wheel
- Loosen the nut or screw that holds the steering wheel
- Insert puller jaws through the narrow puller slots
- Position the jaws below the steering wheel correctly
- Use a ratchet or a claw wrench to turn the hexagon on the spindle head until the component is loosened

MASTER DATA

GTIN [GTIN]	4021176014208
Country of origin	DE
Material	Tool steel
Series	33
Gross weight [kg]	0,745 kg
Package contents	1 piece
Packaging Act	PAPPE PAP 21
Worldwide sales capability	Yes (REACH, RoHS, POP, PROP65, TSCA)

SPARE PARTS

- 033001_short jaws
- 033003_long puller
- 612140_Double-sided spindle tip
- 614135_Mechanical Drive Spindle