

Zylinderschrauben mit Innensechskant DIN 912

12.9 blank

Größe	Steigung	Innensechskant	Kopfhöhe	Kopfdurchmesser	Kernlochbohrer	Durchgangsloch	Längen
						(mittel)	
M2	0,4	1,5	2	3,8	1,6	2,4	4, 5, 6, 8, 10, 12
M2,5	0,45	2	2,5	4,5	2,05	2,9	6, 8, 10, 12
M3	0,5	2,5	3	5,5	2,5	3,4	6, 8, 10, 12, 14, 16, 18, 20, 25, 30, 35
M4	0,7	3	4	7	3,3	4,5	6, 8, 10, 12, 14, 16, 18, 20, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 80
M5	0,8	4	5	8,5	4,2	5,5	6, 8, 10, 12, 14, 16, 18, 20, 22, 25, 30, 35, 40, 45, 50, 60, 70, 90
M6	1	5	6	10	5	6,6	10, 12, 14, 16, 18, 20, 22, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 85, 90, 100, 110, 120, 130
M8	1,25	6	8	13	6,8	9	12, 14, 16, 18, 20, 22, 25, 28, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 85, 90, 95, 100, 110, 120, 130, 140
M10	1,5	8	10	16	8,5	11	16, 20, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 85, 90, 95, 100, 110, 120, 130, 140, 150
M12	1,75	10	12	18	10,2	13,5	20, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 85, 90, 95, 100, 110, 120, 130, 140, 150, 160
M14	2	12	14	21	12	15,5	25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 80, 90, 100, 110
M16	2	14	16	24	14	17,5	30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 90, 100, 110, 120, 130, 140, 150, 160, 180, 200, 220

Größe	Steigung	Innensechskant	Kopfhöhe	Kopfdurchmesser	Kernlochbohrer	Durchgangsloch		Längen
						(mittel)		
M20	2,5	17	20	30	17,5	22		30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 90, 100, 110, 120, 130, 140, 150, 160, 170, 180
M24	3	19	24	36	21	26		60, 70, 80, 90, 100, 110, 120, 130, 140, 150

Maße in mm. Nennmaße; die Toleranzen stehen in der Norm.