DIN 1476 similar to ISO 8746


Round head grooved pins


Round head

Steel | bright | Cr(VI)-free

Further information: DIN standard has been withdrawn







Diameter (d)	d_1		d_3			f	k			r
	min.	max.	nominal size	min.	max.		nominal size	min.	max.	
1.4	1.35	1.4	2.4	2.20	2.60	0.5	0.8	0.70	0.90	1.4
1.6	1.55	1.6	2.8	2.60	3.00	0.5	1.0	0.90	1.10	1.6
2	1.95	2.0	3.5	3.30	3.70	0.5	1.2	1.10	1.30	1.9
2.5	2.42	2.5	4.4	4.20	4.60	0.7	1.5	1.40	1.60	2.4
3	2.92	3.0	5.2	4.95	5.45	1.0	1.8	1.65	1.95	2.8
4	3.90	4.0	7	6.75	7.25	1.5	2.4	2.25	2.55	3.8
5	4.90	5.0	8.8	8.50	9.10	1.5	3.0	2.85	3.15	4.6
6	5.90	6.0	10.5	10.20	10.80	2.0	3.6	3.45	3.75	5.7

Length (l)		
nominal size	min.	max.
3	2.76	3.24
4	3.76	4.24
5	4.76	5.24
6	5.76	6.24
8	7.71	8.29
10	9.71	10.29

Length (l)		
nominal size	min.	max.
12	11.65	12.35
15	14.65	15.35
20	19.58	20.42
25	24.58	25.42

All technical data refer to the measure mm

All technical data without obligation. Subject to technical changes and errors.

DIN 1476 similar to ISO 8746

Round head grooved pins

Round head

Steel | bright | Cr(VI)-free

Diameter	Length (l)									
(d)	3	4	5	6	8	10	12	15	20	25
1.4	●		●							
1.6	●	●	●	●						
2	●	●	●	●	●	●				
2.5		●	●	●	●	●				
3		●	●	●	●	●	●			
4				●	●	●	●	●		
5						●	●	●		
6					●	●	●	●	●	●

All technical data refer to the measure mm

All technical data without obligation. Subject to technical changes and errors.