

Hexagon head bolts DIN 931

10.9 bright

Size	Pitch	Spanner size	Tap drill	Clearance hole (medium)	Lengths
M6	1	10	5	6.6	35, 40, 45, 50, 55, 60, 65, 70, 80, 90
M8	1.25	13	6.8	9	35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 90, 100, 110, 120, 130, 140
M10	1.5	17	8.5	11	40, 45, 50, 55, 60, 65, 70, 75, 80, 90, 100, 110, 120, 130, 140, 150, 160, 170, 180
M12	1.75	19	10.2	13.5	45, 50, 55, 60, 65, 70, 75, 80, 85, 90, 100, 110, 120, 130, 140, 150, 160, 170, 180
M16	2	24	14	17.5	50, 55, 60, 65, 70, 75, 80, 90, 100, 110, 120, 130, 140, 150, 160, 170, 180
M20	2.5	30	17.5	22	65, 70, 75, 80, 90, 100, 110, 120, 130, 140, 150, 160, 170, 180
M24	3	36	21	26	75, 80, 90, 100, 110, 120, 130, 140, 150, 160, 170, 180

Dimensions in mm. Nominal sizes; tolerances are given in the standard.