

Inbusbouten met cilinderkop DIN 912

12.9 blank

Maat	Spoed	Inbussleutel	Kophoogte	Kopdiameter	Kernboor voor tapgat	Doorlaatgat (middel)	Lengtes
M2	0,4	1,5	2	3,8	1,6	2,4	4, 5, 6, 8, 10, 12
M2,5	0,45	2	2,5	4,5	2,05	2,9	6, 8, 10, 12
M3	0,5	2,5	3	5,5	2,5	3,4	6, 8, 10, 12, 14, 16, 18, 20, 25, 30, 35
M4	0,7	3	4	7	3,3	4,5	6, 8, 10, 12, 14, 16, 18, 20, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 80
M5	0,8	4	5	8,5	4,2	5,5	6, 8, 10, 12, 14, 16, 18, 20, 22, 25, 30, 35, 40, 45, 50, 60, 70, 90
M6	1	5	6	10	5	6,6	10, 12, 14, 16, 18, 20, 22, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 85, 90, 100, 110, 120, 130
M8	1,25	6	8	13	6,8	9	12, 14, 16, 18, 20, 22, 25, 28, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 85, 90, 95, 100, 110, 120, 130, 140
M10	1,5	8	10	16	8,5	11	16, 20, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 85, 90, 95, 100, 110, 120, 130, 140, 150
M12	1,75	10	12	18	10,2	13,5	20, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 85, 90, 95, 100, 110, 120, 130, 140, 150, 160
M14	2	12	14	21	12	15,5	25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 80, 90, 100, 110
M16	2	14	16	24	14	17,5	30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 90, 100, 110, 120, 130, 140, 150, 160, 180, 200, 220
M20	2,5	17	20	30	17,5	22	30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 90, 100, 110, 120, 130, 140, 150, 160, 170, 180
M24	3	19	24	36	21	26	60, 70, 80, 90, 100, 110, 120, 130, 140, 150

Maten in mm. Nominale maten; de toleranties staan in de norm.