

Hexagon head screws ISO 4017

8.8 zinc-plated thick-film passivated

Size	Pitch	Head height	Tap drill	Clearance hole (medium)	Lengths
M4	0.7	2.8	3.3	4.5	8, 10, 12, 16, 18, 20, 25, 30, 35, 40
M5	0.8	3.5	4.2	5.5	8, 10, 12, 14, 16, 18, 20, 22, 25, 30, 35, 40, 45, 50
M6	1	4	5	6.6	8, 10, 12, 14, 16, 18, 20, 22, 25, 30, 35, 40, 45, 50, 55, 60, 65
M8	1.25	5.3	6.8	9	12, 16, 18, 20, 22, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 80
M10	1.5	6.4	8.5	11	16, 18, 20, 22, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 90
M12	1.75	7.5	10.2	13.5	20, 25, 30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 90, 100
M16	2	10	14	17.5	30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 90, 100
M20	2.5	12.5	17.5	22	30, 35, 40, 45, 50, 55, 60, 65, 70, 75, 80, 90, 100, 110, 120
M24	3		21	26	40, 55, 65, 70, 80, 90

Dimensions in mm. Nominal sizes; tolerances are given in the standard.